

**POWER PANEL**  
**R1-PWR-30-2X15-220**  
**RUMEL, INC**  
**[WWW.RUMEL-ONLINE.COM](http://WWW.RUMEL-ONLINE.COM)**  
**540-338-3252**

OPERATIONAL/MANUAL

The R1-PWR-30-2X15-220 Power Panel was designed to provide a dual output at 220VAC @ 15 Amps with a 220 VAC @ 30 Amps single input. This interface is provided in a 1U by 19" Rackmount chassis, meeting certifications of UL, CSA, and CE requirements.

Upon mounting the panel in a 19" rack, plug the panel into a 220 VAC source. Through a common switch handle flip the two 250VAC 30 Amp circuit breakers. The lamps should light up accordingly, and 220VAC at 15 Amps is provided at output connectors P2 and P3.

Electrical Ratings

Input Voltage - 220 VAC  
Input Current - 30 Amps  
Frequency - 50 - 60 Hz

Output Voltage -220 VAC  
Output Current - 15 Amps  
Frequency - 50 - 60 Hz

Safety Standards

1. **CAUTION:** Disconnect all power before servicing.
2. **WARNING:** Risk of Electrical Shock.
3. **CAUTION:** Disconnection of the Protective Earth Conductor, may impair the protection provided by the system.

General Standards

1. There are no user serviceable parts.
2. The mains outlet that is utilized to power the equipment must be within 3 Meters of the device and shall be easily accessible.
3. There shall be no switches or disconnect devices in the earth conductor.
4. When transporting the unit, it shall be fully protected with bubble pack or equivalent and flow pack. Use 200 pound test minimum for box.
5. Storage of unit. Unit must be stored indoors with adequate cover or left in shipping container until used.

Warranty : One year from date of shipment.