

POWER PANEL
RI-PSTR-12x12-220
RUMEL, INC
WWW.RUMEL-ONLINE.COM
540-338-3252

OPERATIONAL MANUAL

The RI-PSTR-12x12-220 Power Distribution Panel was designed to provide power distribution for 12 connections at a total power of up to 15 Amps at 220VAC.. This interface is provided in a 1U by 19" Rackmount chassis, meeting certifications of UL, CSA, and CE requirements.

Upon mounting the panel in a 19" rack, plug the panel into a 220 VAC source. The LED will illuminate when power is applied.

Electrical Ratings

Input Voltage - 220 VAC
Input Current - 15 Amps Max
Frequency - 50 - 60 Hz

Output Voltage -220 VAC
Output Current - 15 Amps Max
Frequency - 50 - 60 Hz

Safety Standards

1. **CAUTION:** Disconnect all power before servicing.
2. **WARNING:** Risk of Electrical Shock.
3. **CAUTION:** Disconnection of the Protective Earth Conductor, may impair the protection provided by the system.

General Standards

1. There are no user serviceable parts.
2. There shall be no switches or disconnect devices in the earth conductor.
3. When transporting the unit, it shall be fully protected with bubble pack or equivalent and flow pack. Use 200 pound test minimum for box.
4. Storage of unit. Unit must be stored indoors with adequate cover or left in shipping container until used.

Warranty : One year from date of shipment.